

SANDMARTIN, KINGFISHER & KITE

Level access, bath replacement, cut to length to suit.

- A showering solution where a bathtub is no longer practical, for users with mobility difficulties or requiring wheelchair access.
- 18mm tiling lip can accommodate wallboards or wall tiles. Also used to secure the shower tray to the wall.
- Reinforced GRP construction.
- Suitable for wooden or solid floor situations. Requires floor excavation of approximately **40mm**. The void beneath the shower tray must be filled with a 'weak' sand and cement mix.
- Cut to length tray, incorporating drying area, can be cut from its original length of 1850mm to fit exactly into the space left by a bath. End plate supplied to conceal the cut end.
- Lifetime guarantee.
- Service pipe ducting available as an optional accessory to overcome pipework or to make the showering area larger.
- Anti-slip surface for an assured underfoot grip.
- Exclusively incorporates Biomaster antibacterial protection.
- Left or right hand tray options available.













Cut to length.









	Reference	Tray Size			Cut to Length
		Α	В	С	
	SANDMARTIN	1850	700	1070	From 1850 to 1120mm
	KINGFISHER	1850	800	1170	From 1850 to 1220mm
	KITE	1850	900	1225	From 1850 to 1295mm

All tray's are handed.

	Suits wooden floors	900	Supplied with STW8B-95 gravity waste
	Suits screeded floors	*	UPSW-3-22 Pumped waste available
L E V E L ACCESS	No height difference from the floor	TI	Cut to length bath replacement

Waste details





- Flow rate in excess of 26 litres per minute in 15mm head of water.
- UPSW-3-22 available if using in a waste pump situation.





SANDMARTIN, KINGFISHER & KITE

Shower tray options illustrated below.

